




MECHANICS (ME10001)

Tutorial 2: Equilibrium - I



1. Draw the Free Body Diagram (FBD) of all members (including the pulley) assuming all contacts to be frictionless.

2. An aircraft of weight W is climbing at a constant speed at an angle θ under a constant thrust T against a net air drag R (collinear with T). Given that T is only a function of R and W , complete the FBD keeping in view the concept of equilibrium.





3. The 100 kg wheel rests on a rough surface and bears against the frictionless roller A when the couple M is applied. If $M=60$ Nm and the wheel does not slip, compute the reaction on the roller A.

Ans. $F_A = 231$ N

4. Determine the force P required to begin rolling the uniform cylinder of mass m over the obstruction of height h .

Ans. $P = \frac{mg\sqrt{2rh - h^2}}{r - h}$




5. The spring of modulus $k=3.5$ kN/m is stretched 10 mm when the disk center O is in the leftmost position $x=0$. Determine the tension T required to position the disk center at $x=150$ mm. At that position, what is the normal force N exerted on the horizontal frictionless guide? The mass of the disk is 3 kg.

Ans. $T = 328$ N, $N = 203$ N up



6. Three loads are applied to a light beam supported by cables attached at B and D knowing that the maximum allowable tension in each cable is 12kN and neglecting the weight of the beam, determine the range of values of Q for which the loading is safe when $P = 5$ kN.

Ans: $1.5\text{kN} \leq Q \leq 9\text{kN}$



7. Consider the truss. If the roller at B can sustain a maximum load of 3kN, determine the largest magnitude of each of the three forces F that can be supported by the truss.

Ans: $F=354\text{ N}$




8. Two identical smooth tubes A and B, each of weight W, are suspended at their ends by cords of equal length. A third tube C of weight $W_c = 0.8W$ is placed between A and B. Determine the greatest weight of C that can be supported without upsetting equilibrium.

Ans: $W_c = 0.8W$

9. A vertical load P is applied at the end B of rod BC. The spring constant of the spring is K and the spring is unextended when $\theta = 0$.

- Neglecting the weight of the rod, express the angle θ corresponding to the equilibrium position in terms of P, K and l.
- Determine the value of θ corresponding to the equilibrium if $P = 2Kl$.

Ans: $\theta = \tan^{-1}(P/Kl)$, $\theta = 63.44^\circ$





10. The lightweight cart of the exercise machine shown is supported by a cable whose other end is pulled by the athlete to raise the cart. In the configuration shown with $\beta=18^\circ$, determine the pulling force P applied by the athlete on the cable to maintain equilibrium on the frictionless ramp. Also determine the reaction force R on the cart from the ramp. Take mass of the athlete as 70 kg and $\theta=15^\circ$.

Ans: $P = 91\text{ N}$, $R = 691\text{ N}$

11. The hook wrench is used to turn shafts and collars. If a moment of 80 Nm is required to turn the 200 mm diameter collar about its center O, determine the contact force R on the smooth surface at A. The engagement of the pin at B may be considered to occur at the periphery of the collar.

Ans. $R = 1047\text{ N}$



12. A special jig consists of an 80 Mg sector mounted on a line of rollers at A and a line of rollers at B. One of the rollers at B is a gear which meshes with a ring of gear teeth on the sector so as to turn the sector about its geometric center O. When $\alpha=0$, a counterclockwise torque of 2460 Nm must be applied to the gear at B to keep the assembly from rotating. When $\alpha=30^\circ$, a clockwise torque of 4680 Nm is required to prevent rotation. Locate the mass center G of the jig by calculating \bar{r} and θ . Note that the mass center of the pipe section is at O.

Ans. $\bar{r} = 367\text{ mm}$, $\theta = 79.8^\circ$